



"Where heat transfer vinyl
meets boundless creativity"

TECHNICAL DATA SHEET

Updated March 2025

2D JELLYFISH PATTERN MICRO ELASTIC LETTERING FILM HTV



SM02



SM03




SM04



SM05



SM06



SM07



SM08

PRODUCT COMPOSITION

PET Layer 33.9%
Sticker Layer 10.2%
Color Layer 39.0%
Hot Melt Adhesive Layer 16.9%

APPLICABLE MACHINES

Cutting Plotter, Film Cutting
Machine, Laser Cutting Machine,
Marking Machine, Die-Cutting
Machine

AVAILABLE SIZE

0.5*25m (customizable size)

THICKNESS

Overall Thickness: 0.295mm
PET Thickness: 0.1mm
Sticker Layer: 0.03mm
Color Layer Thickness: 0.115mm
Hot Melt Adhesive Thickness:
0.05mm

APPLICATION METHOD

Hot stamping
temperature/time/pressure:
135°C~140°C/12-15S/4-6KG/Mpa

PEELING METHOD

Warm Peel

WASHING FASTNESS

Grade 4.5, National Standard
Grade 3.5

DRYING TEMPERATURE

Below 60° C

APPLICABLE TEXTILES

Pure Cotton, Polyester,
Poly/Fabric Blended

APPLICATION SCOPE

Clothing, Shoes And Hats,
Luggage And Other Items