



"Where Heat Transfer Vinyl
meets boundless creativity"


TECHNICAL DATA SHEET

Updated March 2025

GLOSSY CHAMELEON HEAT TRANSFER VINYL




ADC08



ADC09




ADC10



AD11



ADC12



ADC13

PRODUCT COMPOSITION

PET Layer 45.5%
Sticker Layer 9.0%
Metal Angle Color Changing Layer
20.45%
Hot Melt Adhesive Layer 22.72%

APPLICABLE MACHINES

Cutting Plotter, Film Cutting
Machine, Laser Cutting Machine,
Marking Machine, Die-Cutting
Machine

AVAILABLE SIZE

0.5*25m (customizable size)

THICKNESS

Overall Thickness: 0.22mm
PET Thickness: 0.1mm
Sticker Layer: 0.02mm
Adhesive Color Layer Thickness:
0.045mm
Hot Melt Adhesive Thickness:
0.05mm

APPLICATION METHOD

Hot stamping
temperature/time/pressure:
145°C~150°C/12-15S/4-6KG/Mpa

PEELING METHOD

Warm Peel

WASHING FASTNESS

Grade 4.5, National Standard
Grade 3.5

DRYING TEMPERATURE

Below 60° C

APPLICABLE TEXTILES

Pure Cotton, Polyester,
Poly/Fabric Blended

APPLICATION SCOPE

Clothing, Shoes And Hats,
Luggage And Other Items