



"Where heat transfer vinyl meets boundless creativity"

TECHNICAL DATA SHEET

Updated March 2025

PU CAMOUFLAGE LEOPARD GRAIN FILM HTV



DDDP01



DDDP02



DDDP03




DDDP04



DDDP05



DDDP06



DDDP07



DDDP08



DDDP09



DDDP10



DDDP11



DDDP12



DDDP13



DDDP14



DDDP15



DDDP16

PRODUCT COMPOSITION

PET Layer 45.5%
Sticker Layer 9.1%
Color Layer 22.7%
Hot Melt Adhesive Layer 22.7%

APPLICABLE MACHINES

Cutting Plotter, Film Cutting Machine, Laser Cutting Machine, Marking Machine, Die-Cutting Machine

AVAILABLE SIZE

0.5*25m (customizable size)

THICKNESS

Overall Thickness: 0.22mm
PET Thickness: 0.1mm
Sticker Layer: 0.02mm
Color Layer Thickness: 0.05mm
Hot Melt Adhesive Thickness: 0.05mm

APPLICATION METHOD

Hot stamping
temperature/time/pressure:
145°C~150°C/12-15S/4-6KG/Mpa

PEELING METHOD

Warm Peel

WASHING FASTNESS

Grade 4.5, National Standard
Grade 3.5

DRYING TEMPERATURE

Below 60° C

APPLICABLE TEXTILES

Pure Cotton, Polyester,
Poly/Fabric Blended

APPLICATION SCOPE

Clothing, Shoes And Hats,
Luggage And Other Item